

Model	Weight (lbs)	Length In.(mm)	Kw 240/120v, 60HZ, 10ph, 40C amb			125C EFF%
			125C	105C	80C	
LT3-75/4	70	9.8 (248)	4.5	4	3.5	76.5
LT3-100/4	84	10.7 (273)	6	5.5	4.8	77.5
LT3-110/4	88	11.1 (283)	6.5	6	5.3	78
LT3-130/4	101	11.9 (303)	7.5	7	6	78.6
LT3-160/4	121	13.1 (303)	10	9	8	79.2

Model	Weight (lbs)	Length In.(mm)	Kw 240/120v, 60HZ, 10ph, 40C amb			125C EFF%
			125C	105C	80C	
LT3-75/4	70	9.8	3.5	3.3	2.8	75.8
LT3-100/4	84	10.7	4.5	4	3.5	76.5
LT3-110/4	88	11.1	5	4.5	4	76.8
LT3-130/4	101	11.9	6	5.5	4.8	77.5
LT3-160/4	121	13.1	8	7.3	6	78

Units are not dual frequency, separate winding required for 50Hz.

Capacitor excited machines specifically for Metal Halide light tower lamps.

For custom voltages or non-standard lamp striking voltages, please refer to *DiPerk*

2 Pole version of above generators available. Please refer to *DiPerk*