

Model	Weight (lbs)	Leads	AVR	Kw 60Hz, 0.8 PF		50Hz, 0.8PF	IP45 COEFF
				480/277V	208/120V	400/230V	
				95/50C	95/50C	95/50C	
ECP3-1S/4	139	12	SR7/2	5.2	4.1	4.3	0.846
ECP3-2S/4	154	12	SR7/2	6.4	5.3	5.3	0.812
ECP3-1L/4	180	12	SR7/2	8.8	7.3	7.3	0.818
ECP3-2L/4	202	12	SR7/2	10.7	8.2	9	0.815
ECP3-3L/4	211	12	SR7/2	12	9.5	10	0.8
ECP28-S/4	235	12	SR7/2	13.5	11.7	11.3	0.853
ECP28-M/4	268	12	SR7/2	16	13.8	13.3	0.85
ECP28-2L/4	306	12	SR7/2	20	17.3	16.6	0.84
ECP28-VL/4	363	12	SR7/2	24	21.8	20	0.8
ECO32-2S/4	438	12	SR7/2	28	27	23	0.829
ECO32-3S/4	471	12	SR7/2	34	32	27	0.8
ECO32-1L/4	546	12	SR7/2	40	39	34	0.8
ECO32-2L/4	620	12	SR7/2	48	43	40	0.833
ECO32-3L/4	656	12	SR7/2	56	48	46	0.8
ECP34-1S/4	750	12	DSR	68	63	57	0.765
ECP34-2S/4	922	12	DSR	84	76	70	0.81
ECP34-1L/4	979	12	DSR	103	88	86	0.8
ECP34-2L/4	1080	12	DSR	119	97	100	0.8
ECP34-3L/4	1089	12	DSR	125	105	105	0.8
ECO38-1SN/4	1122	12	DSR	146	139	119	0.805
ECO38-2SN/4	1232	12	DSR	159	152	133	0.8
ECO38-3SN/4	1298	12	DSR	179	172	150	0.8
ECO38-1LN/4	1496	12	DSR	199	192	166	0.8
ECO38-2LN/4	1683	12	DSR	239	217	199	0.8
ECO38-3LN/4	1991	12	DSR	279	254	233	0.8
ECO40-1S/4	2288	12	DSR	318	276	266	0.825
ECO40-2S/4	2460	12	DSR	358	318	299	0.822
ECO40-3S/4	2576	12	DSR	398	357	332	0.82
ECO40-1L/4	2913	12	DSR	438	376	366	0.818
ECO40-1.5L/4	3036	12	DSR	494	441	412	0.774
ECO40-2L/4	3489	12	DSR	542	477	451	0.735
ECO40-VL/4	3725	12	DSR	582	516	478	0.772
ECO43-1SN/4	4114	12	DSR	638	587	531	0.775
ECO43-2SN/4	4598	12	DSR	741	679	618	0.785
ECO43-1LN/4	5269	12	DSR	877	797	730	0.772
ECO43-2LN/4	5852	12	DSR	1036	963	863	0.77
ECO46-1S/4	6094	12	DSR	1195	NA	996	0.733
ECO46-2S/4	7568	12	DSR	1434	NA	1195	0.722
ECO46-1L/4	8514	12	DSR	1674	NA	1394	0.729
ECO46/2L/4	9350	12	DSR	1992	NA	1660	0.7

Marine agency certified alternators require certified shaft steel, consult factory for lead time.

This must be specified at time of order entry.

All marine alternators have an auxiliary winding 'standard' with 300% short circuit capability.

Space heaters are standard, but may not be required below 100 kW.

IP23 drip proof housing standard.

Use the IP45 Coefficient to properly size the machine for IP45 protection.

Information required with order: Vessel Name, Hull Number, and Shipyard location