

125/40C R/R, 0.8 PH 3 Phase

MODEL	Weight (lbs)	LEADS	138/240-27760Hz		115/200-230/400v 50Hz	
			Kw	EFF%	Kw	EFF%
NPE 32-A/4	169	12	7.2	80.4	6	80.1
NPE 32-B/4	182	12	11.2	81.6	9.2	81.4
NPE 32-C/4	198	12	12.8	82.1	10.4	81.9
NPE3 2-D/4	224	12	16.8	82.7	13.6	82.5
NPE 32-E/4	264	12	24.8	83.3	20	83.1
NPE 32-F/4	295	12	27.2	84	22	83.8

105/40C R/R 0.8PF 3 Phase

MODEL	Weight (lbs)	LEADS	138/240-27760Hz		115/200-230/400v 50Hz	
			Kw	EFF%	Kw	EFF%
NPE 32-A/4	169	12	6.7	80.5	5.8	80.2
NPE 32-B/4	182	12	10	81.7	8.4	81.5
NPE 32-C/4	198	12	11.6	82.2	9.6	82
NPE3 2-D/4	224	12	15.2	82.8	12.4	82.6
NPE 32-E/4	264	12	22.8	83.4	18.4	83.2
NPE 32-F/4	295	12	24.8	84.1	20	83.9

125/40C R/R, 1.0 PF 1 Phase (Dedicated Winding)

MODEL	Weight (lbs)	LEADS	138/240-27760Hz		115/200-230/400v 50Hz	
			Kw	EFF%	Kw	EFF%
NPE 32-A/4	165	4	8.4	78.9	6.4	78.8
NPE 32-B/4	178	4	10.5	79.1	8.7	79
NPE 32-C/4	194	4	13	79.7	10.8	79.6
NPE3 2-D/4	220	4	17	80.4	13.8	80.3
NPE 32-E/4	260	4	22	80.9	18.5	80.8
NPE 32-F/4	290	4	26.5	81.9	22.5	81.7

104/40C R/R 1.08 PF 1 Phase (Dedicated Winding)

MODEL	Weight (lbs)	LEADS	138/240-27760Hz		115/200-230/400v 50Hz	
			Kw	EFF%	Kw	EFF%
NPE 32-A/4	165	4	8	79	6.2	78.9
NPE 32-B/4	178	4	10	79.2	8.3	79.1
NPE 32-C/4	194	4	12.5	79.8	10.4	79.7
NPE3 2-D/4	220	4	16	80.5	13.3	80.4
NPE 32-E/4	260	4	21	81	17.5	80.9
NPE 32-F/4	290	4	25	82	21	81.8